

# VP 1340A Value Vibratory Soil Plate, 13 kN, 40mm/15.5in

Item Number: 0009031

# VP 1340A

## Application

>> Designed for compaction in confined areas of granular soil in narrow trenches. These plates are ideal for curbs, gutters, around tanks, forms, columns, footings, guard railings, drainage ditches, gas and sewer works and building construction. <<



## Additional Advantages

- Special contoured running surfaces and rounded edges provide maximum performance and maneuverability
- Completely enclosed belt protected by a lightweight beltguard for reduced wear and minimal service.
- Newly designed “low-vibration” guide handle greatly improves operator comfort and minimizes operator fatigue.
- Heavy-duty shockmounts on engine console dampen vibrations thereby reducing wear on the components.
- Exciter bearing design requires minimal maintenance for improved productivity.
- Ergonomically designed lifting handles offer easier loading and unloading for operator during transport.
- Improved water tank design with larger capacity and filler hole provide higher productivity

Description	Metric	Imperial
Length x width x height	1.070 x 400 x 911 mm	42 x 16 x 36 in
Lowest working height	680 mm	26.5 in
Size of base plate (L x W)	588 x 400 mm	23 x 15,5 in
Operating weight	74 kg	163 lb
Shipping weight (including packaging)	77 kg	171 lb
Shipping size	675 x 535 x 800 mm	27 x 21 x 32 in
Compacted area (soil)	up to 550 m <sup>2</sup> /h	up to 5,900 ft <sup>2</sup> /h
Forward speed (soil)	up to 23 m/min	up to 75 ft/min
Max. gradeability (depending on soil)	up to 30 %	up to 30 %
Vibration frequency	97 Hz	5,800 vpm
Max. centrifugal force	13 kN	2,925 lbf
Engine Type	air-cooled, 4 cycle single cylinder, gasoline engine Honda	air-cooled, 4 cycle single cylinder, gasoline engine Honda
Type	Honda	
Displacement	163 cm <sup>3</sup>	9.9 in <sup>3</sup>
Max. power output (DIN-ISO 3046*)	4,1 kW	5.5 hp
at	3.900 1/min	3.900 rpm
Rated power output	3.6 kW	4.8 hp
at	3,600 1/min	3,600 rpm
Fuel tank capacity	3.6 l	3.8 US qt
Fuel consumption	1.8 l/h	1.9 US qt/h
Power Train	Power transmission from engine via centrifugal clutch and V-belt onto exciter which transmits centrifugal force onto baseplate.	

### Standard Package - VP 1340A

includes operator's manual and parts book.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Friday, November 12, 2010

