

# Easy Screed Pro

## Free Screeder



### High Performance Professional Free Screeder

- Adjustable centrifugal force from the vibrator unit
- In-line flexible drive shaft for ultimate durability and reliability
- High power 4 stroke Honda engine for high performance and reliability
- Height adjustable handles for operator comfort and control
- Different Beam lengths to suit application
- Isolators ensure vibration is transmitted to the concrete and not the operator



[www.BelleGroup.com](http://www.BelleGroup.com)

No.1 for Light Construction Equipment



COMPACTING...

MIXING...

CONCRETING...

CUTTING...

BREAKING...

MOVING

A high performance 'free screeding' machine. Ultimately designed for levelling and vibrating concrete slabs without the need to run off support formwork. The drive unit provides control and high power vibration to a reinforced aluminium beam. The tool free removing and reversing of the uniquely shaped beam also allows 'striking off' across traditional formwork

## Technical Specifications

|                  |                            |      |
|------------------|----------------------------|------|
| <b>Model</b>     | <b>Easy Screenshot Pro</b> |      |
| Part No.         | 157.9.010                  |      |
| Engine Power     | (watts)                    | 1100 |
| Frequency        | (Hz)                       | 83   |
| Compaction Depth | (mm)                       | 75   |
| Width            | (mm)                       | 630  |
| Height           | (mm)                       | 440  |
| Length           | (mm)                       | 1040 |
| Weight           | (kg)                       | 16   |
| <b>Model</b>     | <b>1.5m Beam</b>           |      |
| Part No.         | 157.3.000                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 6    |
| <b>Model</b>     | <b>1.9m Beam</b>           |      |
| Part No.         | 157.3.001                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 8    |
| <b>Model</b>     | <b>2.5m Beam</b>           |      |
| Part No.         | 157.3.002                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 10.5 |
| <b>Model</b>     | <b>3m Beam</b>             |      |
| Part No.         | 157.3.003                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 12.5 |
| <b>Model</b>     | <b>3.75m Beam</b>          |      |
| Part No.         | 157.3.004                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 15.5 |
| <b>Model</b>     | <b>4.25m Beam</b>          |      |
| Part No.         | 157.3.005                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 17.5 |
| <b>Model</b>     | <b>5m Beam</b>             |      |
| Part No.         | 157.3.006                  |      |
| Width            | (mm)                       | 200  |
| Height           | (mm)                       | 100  |
| Weight           | (kg)                       | 20.5 |



In-line Flexible Drive Shaft



Height Adjustable Handles



Adjustable Centrifugal Force



Honda Petrol With Oil Alert



Easily Transported Around Sites



Different Beam Lengths To Suit Application



Belle Group Head Office  
 Sheen, Nr. Buxton  
 Derbyshire, SK17 0EU  
 Tel: (+44) 01298 84606  
 Fax: (+44) 01298 84722  
 Email: sales@belle-group.co.uk

Dealer Stamp:

www.BelleGroup.com

Belle Group reserve the right to amend or improve any specifications in this brochure without notice.