## MultiTrack



**Ground**Guards®

+44 (0)113 267 6000 info@ground-guards.co.uk www.ground-guards.co.uk

## MultiTrack











fully recyclable

Overall Size: 2435 x 1215 x 13mm (plus treads)

Surface Area: 2.95m<sup>2</sup>

Weight: 39kg

Tread Options: Roadway,

Walkway and Smooth, or a combination

Connectors: 10 joining points.

A choice of standard clip joiners, low profile joiners or bolted joiners,

plus anchor pins

Packed in: Stillage of 25 mats

Stillage Pack: Weight: 1105kg

Dimensions:

2550 x 1260 x 900mm

Fire Rating: UL94 HB

Slip Testing: BS7976 part 2

Deflection: Tested on varying CBR ground conditions using a 300mm diameter steel

platen with 6 tonnes load to simulate the pressure of an HGV wheel

Ground CBR 11.35%: Deflection 17.68mm

Ground CBR 8.58%: Deflection 20.41mm

Ground CBR 4%: Deflection 22.00mm

## **Guarantee:**

MultiTrack temporary roadway mats are guaranteed for life against breakage up to 120 Tonnes UDL (Uniformly Distributed Load).

It is the user's responsibility to assess the load-bearing capacity of the ground, and to only operate vehicles within the weight that the ground is capable of safely supporting. Ground-Guards Ltd accepts no liability whatsoever for any damage, loss or injury arising from the ground conditions on which these products are used.

MultiTrack mats are not suitable to use for bridging purposes. Damage caused by mechanical equipment (e.g. cuts by digger buckets) or sharp protrusions beneath the mats is not covered by this guarantee.



Roadway

Walkway

Smooth

**Ground**Guards®

+44 (0)113 267 6000 info@ground-guards.co.uk www.ground-guards.co.uk