

Compact Track Loaders / T76 Compact Track Loader

T76 Loader Specifications & Options

Review the T76 compact track loader specs and compare with other models.

■ Standard ☑ Optional N/A Not Applicable

Units METRIC

Bobcat T76

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (ISO)	2,900 lb
Operating Capacity (50% of Tip)	4143 lb
Tipping Load	8285 lb
Operating Weight	10250 lb
Travel Speed	6.8 mph
Travel Speed (2-speed option)	9.2 mph
Ground Pressure (Rubber)	6.2 psi

Capacities

Fuel Tank	31.7 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23.3 gal/min
Auxiliary High Flow	30.3 gal/min

Dimension

Length	147.1 in
Length without Attachment	113.9 in
Length with Standard Bucket	147.1 in
Width	72.9 in
Width (with bucket)	74 in
Height	81.8 in
Height with Operator Cab	81.8 in
Height to Bucket Hinge Pin	128.3 in
Reach @ Maximum Height	39.9 in
Turning Radius	89.3 in
Length of track on ground	59.2 in
Track Width	12.6 in
Track Width - Optional	17.7 in

Features

Joystick Control	<input type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	N/A
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	N/A
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.