

Product range		DLT 1304							
Type		C85-14	C95-12	C100-10	C110-9	C105-14	C115-12	C130-10	C140-9
<b>Operational data</b>									
Volume flow <sup>1)</sup>	m <sup>3</sup> /min	8.6	9.4	10.0	10.8	10.5	11.5	12.5	13.3
	cfm	304	332	353	381	371	406	441	470
Operating pressure range	bar	5 - 14	5 - 12	5 - 10	5 - 8.6	5 - 14	5 - 12	5 - 10	5 - 8.6
	psi	73 - 203	73 - 174	73 - 145	73 - 125	73 - 203	73 - 174	73 - 145	73 - 125
<b>Engine</b>		Deutz TCD 4.1 L4							
Installed engine power	kW	90	90	90	90	105	105	105	105
RPM-range	rpm	1300 - 1850	1300 - 2000	1300 - 2100	1300 - 2300	1300 - 1750	1300 - 1900	1300 - 2050	1300 - 2200
<b>Operating weight <sup>2)</sup></b>									
<b>Portable compressor</b>									
	adjustable towbar braked kg	2075	2075	2075	2075	2160	2160	2160	2160
	straight towbar braked kg	2000	2000	2000	2000	2085	2085	2085	2085
<b>Permissible gross weight</b>	kg	2500	2500	2500	2500	2500	2500	2500	2500
<b>Filling capacities</b>									
Engine oil	l	11.5	11.5	11.5	11.5	11.5	11.5	11.5	11.5
Diesel tank	l	175	175	175	175	175	175	175	175
Adblue tank capacity	l	20	20	20	20	20	20	20	20
Compressor oil	l	20	20	20	20	25.5	25.5	25.5	25.5
<b>Dimensions and connections</b>									
Length	adjustable towbar braked mm	4447 - 4671	4447 - 4671	4447 - 4671	4447 - 4671	4447 - 4659	4447 - 4659	4447 - 4659	4447 - 4659
	straight towbar braked mm	4294	4294	4294	4294	4294	4294	4294	4294
Width	mm	1820	1820	1820	1820	1820	1820	1820	1820
Height	mm	1884	1884	1884	1884	1884	1884	1884	1884
Compressed air outlet		2 x ¾" and 1 x 2"							
<b>Sound level</b>									
Sound pressure level <sup>3)</sup>	dB(A) LPA	70	70	70	70	70	70	70	70

<sup>1)</sup> Acc. to ISO 1217 Ed. 4 2009 Annex D <sup>2)</sup> Operating weight without options <sup>3)</sup> Noise level acc. to PNEUROP PN8NTC2.2 at 7 m