

| Product range | | DLT 2703 | | | | | | | | DLT 2703 HP | | |
|--|---------------------|---------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------------|-----------|-----------|
| Type | | C200TS-14 | C210TS-12 | C220TS-10 | C230TS-9 | C240TS-14 | C250TS-12 | C260TS-10 | C270TS-9 | C200TS-24 | C210TS-21 | C230TS-17 |
| Operational data | | | | | | | | | | | | |
| Volume flow ¹⁾ | m ³ /min | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 20 | 21 | 23 |
| | cfm | 706 | 741.6 | 776.9 | 812 | 847.5 | 882.8 | 918 | 953 | 706 | 741.6 | 812 |
| Operating pressure | bar | 6 - 14 | 6 - 12 | 6 - 10 | 6 - 8.6 | 6 - 14 | 6 - 12 | 6 - 10 | 6 - 8.6 | 14 - 24 | 14 - 21 | 14 - 17 |
| | psi | 203 | 174 | 145 | 130.5 | 203 | 174 | 145 | 130.5 | 348 | 304.5 | 246.5 |
| Engine | | Cummins QSB 6.7 | | | | | | | | Cummins QSB 6.7 | | |
| Installed engine power | kW | 180 | 180 | 180 | 180 | 224 | 224 | 224 | 224 | 224 | 224 | 224 |
| Engine off load speed | rpm | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 |
| Engine full load speed | rpm | 2400 | 2400 | 2400 | 2400 | 2400 | 2400 | 2400 | 2400 | 2400 | 2400 | 2400 |
| Operating weight ²⁾ | | | | | | | | | | | | |
| Portable compressor adjustable towbar braked | kg | 3300 | 3300 | 3300 | 3300 | 3340 | 3340 | 3340 | 3340 | 3340 | 3340 | 3340 |
| Permissible gross weight | kg | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 | 3500 |
| Filling capacities | | | | | | | | | | | | |
| Engine oil | l | 17 | 17 | 17 | 17 | 17 | 17 | 17 | 17 | 17 | 17 | 17 |
| Diesel tank | l | 350 | 350 | 350 | 350 | 350 | 350 | 350 | 350 | 350 | 350 | 350 |
| Adblue tank capacity | l | 38 | 38 | 38 | 38 | 38 | 38 | 38 | 38 | 38 | 38 | 38 |
| Compressor oil | l | 65 | 65 | 65 | 65 | 70 | 70 | 70 | 70 | 55 | 55 | 55 |
| Dimensions and connections | | | | | | | | | | | | |
| Length | mm | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 | 5179-5405 |
| Width | mm | 1960 | 1960 | 1960 | 1960 | 1960 | 1960 | 1960 | 1960 | 1960 | 1960 | 1960 |
| Height | mm | 2636 | 2636 | 2636 | 2636 | 2636 | 2636 | 2636 | 2636 | 2636 | 2636 | 2636 |
| Compressed air outlet | | 3 x 3/4" and 1 x 2" | | | | | | | | 1 x 2" | | |
| Sound level | | | | | | | | | | | | |
| Sound pressure level ³⁾ | dB(A) LPA | 71 | 71 | 71 | 71 | 71 | 71 | 71 | 71 | 71 | 71 | 71 |

¹⁾ Acc. to ISO 1217 Ed. 4 2009 Annex D ²⁾ Operating weight without options ³⁾ Noise level acc. to PNEUROPN8NTC2.2 at 7 m