

Operating data		
Operating weight kg	1,495	1,467
L x W x H mm	1853 x 820 x 1270	1853 x 820 x 1270
Drum diameter mm	520	520
Width Drum mm	560 / 820 *	560 / 820 *
Centrifugal force (min.) kN	34.2	34.2
Centrifugal force (max.) kN	68.4	68.4
Frequency Hz	41.7	41.7
Linear force static (per drum) N/mm	10.2	9.8
Linear force dynamic (per drum) N/mm	45	45
Travel speed forward km/h	2.5	2.5
Travel speed reverse km/h	2.5	2.5
Turning radius inner mm	1,600	1,600
Surface capacity max. (depending on soil consistency) m ² /h	990	990
Gradeability max. (without vibration) %	50	50
Gradeability max. (with vibration) %	45	50
Engine / Motor		
Engine / Motor type	Water-cooled 3-cylinder diesel engine with electric starter	Water-cooled 3-cylinder diesel engine with electric starter
Engine / Motor manufacturer	Kohler KDW 1003	Kubota D902
Displacement cm ³	1,028	898
Operating performance (DIN ISO 3046) kW	14.8	15.5
RPM / speed Operating rpm	3,000	3,000
Fuel type Low Sulfur / Ultra Low Sulfur	Diesel	Diesel
Fuel consumption l/h	4.5	4.5
Tank capacity l	24	24

*RTx model drums can be configured for 32in (820mm) or 22in (560mm) width.

