



PT3A

Self Priming Trash Pump

Tough trash pumps great for a variety of applications

PT pumps are ideal for general dewatering of excavations, flooded basements, manholes, utility vaults, mining work, swimming pools, lakes and barge holds or wherever there is unwanted water. With built-in contractor friendly features, this line of trash pumps has redefined the quality and durability standards of self-priming, centrifugal trash pumps.

Highlights

- Construction grade impeller and volute
- Durable Honda engine
- Central lift point
- Construction grade impeller and volute
- Compact, lightweight design

Technical Data

■ Mechanical - Output Details

flow rate max.	383,1 gal/mi
Solid diameter max.	0,8 "
Suction head max.	26,2 Foot
Delivery height max.	88,6 Foot

■ Mechanical Details

Length	27,8 "
Width	19,9 "
Height	22,4 "
Operating weight	154,8 lb
Intake-/Pressure socket-dia.	3,1 "

■ Engine

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1,0
Cylinder capacity	16,5 Inch3

Kraftstofftyp	Gasoline
tank capacity	1,4 gal US
Power rating max.	7,9 hp
Engine speed (Power max.)	3.600,0 1/min
Operating Engine speed	3.500,0 1/min
Standard (Operating power)	SAE J1349
Manufacturer	Honda
Engine speed 1	3.600,0 1/min
Consumption at Speed 1	0,7 GPH US
Run Time at Speed 1	2,0 hrs

■ Environment Data

Sound power LWA, guaranteed	105,0 dB(A)
-----------------------------	-------------

■ Shipping and Storage

Length for shipping	28,7 "
Width for shipping	20,9 "
Height for shipping	23,6 "
Shipping weight	160,1 lb