

SPECIFICATIONS



Model		E10	E17	E20	E26	E32	E35
GENERAL	Tail Swing Type	Zero	Zero	Zero	Minimal – 3.5 in. (89 mm)	Conv. – 13.4 in. (340 mm)	Zero
	Weight	2593 lb. (1176 kg)	3774 lb. (1712 kg)	4167 lb. (1890 kg)	6489 lb. (2942 kg)	7403 lb. (3358 kg)	7659 lb. (3474 kg)
	Dig Depth	71.7 in. (1820 mm)	87.8 in. (2230 mm)	100.2 in. (2545 mm)	114.4 in. (2906 mm)	121.2 in. (3077 mm)	121.2 in. (3077 mm)
	Reach at Ground Level	121.8 in. (3093 mm)	155.2 in. (3944 mm)	168.8 in. (4287 mm)	191.9 in. (4876 mm)	194.5 in. (4940 mm)	204.3 in. (5190 mm)
	Max. Dump Height	71.6 in. (1818 mm)	97.8 in. (2483 mm)	110.2 in. (2799 mm)	128.8 in. (3272 mm)	137.2 in. (3484 mm)	137.2 in. (3484 mm)
	Track Width	28.0-43.3 in. (710-1100 mm)	38.6-53.5 in. (980-1358 mm)	38.6-53.5 in. (980-1360 mm)	61.0 in. (1550 mm)	61.8 in. (1569 mm)	69.7 in. (1769 mm)
	Ground Pressure	4.2 psi (0.29 bar)	4.2 psi (0.29 bar)	4.2 psi (0.29 bar)	4.1 psi (0.28 bar)	4.7 psi (0.33 bar)	4.6 psi (0.32 bar)
PERFORMANCE	Standard Track Tread Width	7.1 in. (180 mm)	9.1 in. (230 mm)	9.1 in. (230 mm)	11.8 in. (300 mm)	11.8 in. (300 mm)	11.8 in. (300 mm)
	Rated Lift Capacity						
	(Over blade, ground level, 10 ft. (3 m) reach)	527 lb. (239 kg)	807 lb. (366 kg)	1382 lb. (626 kg)	2359 lb. (1070 kg)	2975 lb. (1349 kg)	3318 lb. (1505 kg)
	(Over side, ground level, 10 ft. (3 m) reach)	263 lb. (119 kg)	540 lb. (244 kg)	615 lb. (279 kg)	1016 lb. (461 kg)	1329 lb. (603 kg)	1393 lb. (632 kg)
	Travel Speed: Low/High	1.3/1.7 mph (2.1/2.8 km/hr.)	1.2/2.5 mph (1.9/4 km/hr.)	1.3/2.6 mph (2.1/4.2 km/hr.)	1.8/3.2 mph (2.9/5.2 km/hr.)	1.6/2.9 mph (2.6/4.7 km/hr.)	1.6/2.9 mph (2.6/4.7 km/hr.)
	Tail Swing Type/Overhang	Zero		Zero	Minimal – 3.5 in. (89 mm)	Conv. – 16.9 in. (429 mm)	Minimal – 3.2 in. (81 mm)
	Weight	2593 lb. (1176 kg)	—	4167 lb. (1890 kg)	6489 lb. (2942 kg)	8269 lb. (3752 kg)	8362 lb. (3794 kg)
LONG ARM OPTION PERFORMANCE	Dig Depth	71.7 in. (1820 mm)	—	100.2 in. (2545 mm)	114.4 in. (2906 mm)	133.0 in. (3377 mm)	133.0 in. (3377 mm)
	Reach at Ground Level	121.8 in. (3093 mm)	—	168.8 in. (4287 mm)	191.9 in. (4876 mm)	205.9 in. (5230 mm)	215.8 in. (5480 mm)
	Max. Dump Height	71.6 in. (1818 mm)	—	110.2 in. (2799 mm)	128.8 in. (3272 mm)	144.3 in. (3665 mm)	144.3 in. (3665 mm)
EXTENDABLE ARM OPTION PERFORMANCE	Tail Swing Type/Overhang	—	—	—	—	Conv. – 16.9 in. (429 mm)	Minimal – 3.2 in. (81 mm)
	Weight	—	—	—	—	8497 lb. (3855 kg)	8590 lb. (3897 kg)
	Dig Depth	—	—	—	—	153.2 in. (3892 mm)	153.2 in. (3892 mm)
	Reach at Ground Level	—	—	—	—	225.3 in. (5722 mm)	235.1 in. (5972 mm)
	Max. Dump Height	—	—	—	—	154.5 in. (3925 mm)	154.5 in. (3925 mm)
ENGINE	Emissions Tier (EPA)	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Horsepower	10.2 hp (7.6 kW)	15.0 hp (11.2 kW)	15.0 hp (11.2 kW)	24.8 hp (18.5 kW)	24.8 hp (18.5 kW)	24.8 hp (18.5 kW)
	Engine Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
	Fuel Tank Capacity	4.2 gal. (15.9 L)	5.6 gal. (21.2 L)	5.6 gal. (21.2 L)	9.1 gal. (34.4 L)	13.7 gal. (51.9 L)	13.7 gal. (51.9 L)
	Battery Rundown Protection	—	Std	Std	Std	Std	Std
MACHINE FEATURES & OPTIONS	Angle Blade	—	—	—	—	—	Opt
	Auto-Idle Throttle	—	—	Opt	Std	Std	Std
	Auto-Shift Travel System	—	—	Opt	Std	Std	Std
	Automatic Slew Brake	—	Std	Std	Std	Std	Std
	Blade Float	—	—	Std	Std	Std	Std
	Bolt-On Street Pad	—	—	—	—	—	Opt
	Cab With Heat	—	—	Opt	—	—	—
	Cab With Heat and AC	—	—	—	Opt	Opt	Opt
	Control Pattern Selector Valve	Std	Std	Std	Std	Std	Std
	Deluxe Cloth Seat	—	—	—	Opt	Opt	Opt
	Depth Check	—	—	—	—	Opt	Opt
	Diverter Valve	—	—	—	—	Opt	Opt
	Fingertip Boom Swing Control	—	Std	Std	Std	Std	Std
	Falling Object Protection Structure (FOPS)	—	Std	Std	Std	Std	Std
	Roll Over Protective Structure (ROPS)	Std	Std	Std	Std	Std	Std
	Fold-Down TOPS	Std	—	—	—	—	—
	Fuel Fill Alert	—	Std	Std	Std	Std	Std
	Heated Seat	—	—	—	—	Opt	Opt
	Keyless/Password Start System	Opt	—	—	Opt	Opt	Opt
	Lift Eye	Opt	Std	Std	Opt	Std	Std
	Retractable Undercarriage	Std	Std	Std	—	—	—
	Segmented Tracks	—	—	—	—	—	—
	Steel Tracks	—	—	—	—	—	Opt
FEATURES FOR ATTACHMENTS	Mechanical Pin-Grabber Coupler	—	Opt	Opt	Opt	—	—
	Hydraulic Pin-Grabber Coupler	—	—	—	Opt	Opt	Opt
	Mechanical X-Change Coupler	—	—	—	Std	Std	Std
	Hydraulic X-Change Coupler	—	—	—	—	Opt	Opt
	Pin On Attachment System	Std	Std	Std	—	—	—
	Auxiliary Hydraulic Flow	5.3 gpm (20.0 L/min.)	7.9 gpm (30.0 L/min.)	7.9 gpm (30.0 L/min.)	14.2 gpm (53.8 L/min.)	16.9 gpm (63.9 L/min.)	16.9 gpm (63.9 L/min.)
	Auxiliary Hydraulic Pressure	2756 psi (190.02 bar)	2611 psi (180.02 bar)	2611 psi (180.02 bar)	2611 psi (180.02 bar)	2987 psi (205.94 bar)	2987 psi (205.95 bar)
	Hydraulic Clamp	—	Opt	Opt	Opt	Opt	Opt
	Fingertip Auxiliary Control	—	Std	Std	Std	Std	Std
	Secondary Auxiliary Hydraulics	—	—	—	Opt	Opt	Opt
	Selectable Auxiliary Flow	—	Std	Std	Std	Std	Std

*E40 depth check doesn't have some of the updated features available on other models. Talk to your dealer for details.